

LSPR-R9005-JETBLACK-MATT-400ML

Version 11.0 Revision Date: 22.05.2019 SDS Number: 665410-00003 Date of last issue: 01.03.2019
Date of first issue: 30.11.2012

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : LSPR-R9005-JETBLACK-MATT-400ML

Product code : 0893 329 005

Manufacturer or supplier's details

Company : Wurth Australia Pty Ltd

Address : 2/1 Healey Road
Dandenong South, Victoria, 3175

Telephone : +61 3 8788 1111

Emergency telephone number : 1300 657 765. Advisory office in case of poisoning - National Poisons Centre: 131 126

E-mail address : prodsafe@wuerth.com

Recommended use of the chemical and restrictions on use

Recommended use : Paints

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable aerosols : Category 1

Gases under pressure : Liquefied gas

Serious eye damage/eye irritation : Category 2A

Specific target organ toxicity - single exposure : Category 3

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

LSPR-R9005-JETBLACK-MATT-400ML

Version 11.0 Revision Date: 22.05.2019 SDS Number: 665410-00003 Date of last issue: 01.03.2019
 Date of first issue: 30.11.2012

Supplemental Hazard Statements : AUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**
 P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Pressurized container: Do not pierce or burn, even after use.
 P261 Avoid breathing spray.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear eye protection/ face protection.

Response:
 P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.

Storage:
 P405 Store locked up.
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Acetone	67-64-1	>= 30 -< 60
Butane	106-97-8	>= 10 -< 20
Dimethyl ether	115-10-6	>= 10 -< 20
Propane	74-98-6	>= 10 -< 20
Reaction mass of ethylbenzene and xylene	1330-20-7	< 10
n-Butyl acetate	123-86-4	< 10
2-Methoxy-1-methylethyl acetate	108-65-6	< 10
Isobutyl methyl ketone	108-10-1	< 10
Ethanol	64-17-5	< 10
butyl glycollate	7397-62-8	< 1

LSPR-R9005-JETBLACK-MATT-400ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2019
11.0	22.05.2019	665410-00003	Date of first issue: 30.11.2012

SECTION 4. FIRST AID MEASURES

- | | | |
|---|---|--|
| General advice | : | In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice. |
| If inhaled | : | If inhaled, remove to fresh air.
Get medical attention. |
| In case of skin contact | : | In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse. |
| In case of eye contact | : | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention. |
| If swallowed | : | If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water. |
| Most important symptoms and effects, both acute and delayed | : | Causes serious eye irritation.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking. |
| Protection of first-aiders | : | First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists. |
| Notes to physician | : | Treat symptomatically and supportively. |

SECTION 5. FIREFIGHTING MEASURES

- | | | |
|---------------------------------------|---|--|
| Suitable extinguishing media | : | Water spray
Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : | None known. |
| Specific hazards during fire-fighting | : | Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. |
| Hazardous combustion products | : | Carbon oxides
Nitrogen oxides (NO _x) |

LSPR-R9005-JETBLACK-MATT-400ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2019
11.0	22.05.2019	665410-00003	Date of first issue: 30.11.2012

- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
- Hazchem Code : 2YE
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.
- Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
-

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use with local exhaust ventilation.
Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure potential
- Advice on safe handling : Do not get on skin or clothing.
-

LSPR-R9005-JETBLACK-MATT-400ML

Version 11.0 Revision Date: 22.05.2019 SDS Number: 665410-00003 Date of last issue: 01.03.2019
 Date of first issue: 30.11.2012

Do not breathe vapours or spray mist.
 Do not swallow.
 Do not get in eyes.
 Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
 Keep away from heat and sources of ignition.
 Take precautionary measures against static discharges.
 Take care to prevent spills, waste and minimize release to the environment.

Do not spray on an open flame or other ignition source.

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
 When using do not eat, drink or smoke.
 Wash contaminated clothing before re-use.

Conditions for safe storage : Store locked up.
 Keep in a cool, well-ventilated place.
 Store in accordance with the particular national regulations.
 Do not pierce or burn, even after use.
 Keep cool. Protect from sunlight.

Materials to avoid : Do not store with the following product types:
 Self-reactive substances and mixtures
 Organic peroxides
 Oxidizing agents
 Flammable liquids
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Explosives

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Acetone	67-64-1	STEL	1,000 ppm 2,375 mg/m ³	AU OEL
		TWA	500 ppm 1,185 mg/m ³	AU OEL
		TWA	250 ppm	ACGIH
Butane	106-97-8	STEL	500 ppm	ACGIH
		TWA	800 ppm 1,900 mg/m ³	AU OEL
		STEL	1,000 ppm	ACGIH
Dimethyl ether	115-10-6	TWA	400 ppm 760 mg/m ³	AU OEL
		STEL	500 ppm 950 mg/m ³	AU OEL

LSPR-R9005-JETBLACK-MATT-400ML

Version 11.0 Revision Date: 22.05.2019 SDS Number: 665410-00003 Date of last issue: 01.03.2019
 Date of first issue: 30.11.2012

Reaction mass of ethylbenzene and xylene	1330-20-7	STEL	150 ppm 655 mg/m ³	AU OEL
		TWA	80 ppm 350 mg/m ³	AU OEL
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
n-Butyl acetate	123-86-4	STEL	200 ppm 950 mg/m ³	AU OEL
		TWA	150 ppm 713 mg/m ³	AU OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
2-Methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm 274 mg/m ³	AU OEL
Further information: Skin absorption				
		STEL	100 ppm 548 mg/m ³	AU OEL
Further information: Skin absorption				
Isobutyl methyl ketone	108-10-1	STEL	75 ppm 307 mg/m ³	AU OEL
		TWA	50 ppm 205 mg/m ³	AU OEL
		TWA	20 ppm	ACGIH
		STEL	75 ppm	ACGIH
Ethanol	64-17-5	TWA	1,000 ppm 1,880 mg/m ³	AU OEL
		STEL	1,000 ppm	ACGIH

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Formaldehyde	50-00-0	TWA	1 ppm 1.2 mg/m ³	AU OEL
Further information: Category 2 (Carc. 2) Suspected human carcinogen, Sensitiser				
		STEL	2 ppm 2.5 mg/m ³	AU OEL
Further information: Category 2 (Carc. 2) Suspected human carcinogen, Sensitiser				
		TWA	0.1 ppm	ACGIH
		STEL	0.3 ppm	ACGIH
Methanol	67-56-1	STEL	250 ppm 328 mg/m ³	AU OEL
Further information: Skin absorption				
		TWA	200 ppm 262 mg/m ³	AU OEL
Further information: Skin absorption				
		TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH

LSPR-R9005-JETBLACK-MATT-400ML

Version 11.0 Revision Date: 22.05.2019 SDS Number: 665410-00003 Date of last issue: 01.03.2019
 Date of first issue: 30.11.2012

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
Isobutyl methyl ketone	108-10-1	methyl iso-butyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	1 mg/l	ACGIH BEI
Reaction mass of ethylbenzene and xy-lene	1330-20-7	Methylhip-puric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g cre-atinine	ACGIH BEI

Engineering measures : Processing may form hazardous compounds (see section 10).
 Minimize workplace exposure concentrations.
 Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure potential
 Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Self-contained breathing apparatus

Hand protection

Material : butyl-rubber
 Break through time : >= 30 min
 Glove thickness : 0.7 mm
 Wearing time : <= 15 min

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufactur-

LSPR-R9005-JETBLACK-MATT-400ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2019
11.0	22.05.2019	665410-00003	Date of first issue: 30.11.2012

er. Wash hands before breaks and at the end of workday.

- Eye protection : Wear the following personal protective equipment:
Safety goggles
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
Flame retardant antistatic protective clothing, unless assessment demonstrates that the risk of explosive atmospheres or flash fires is low.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Aerosol containing a liquefied gas
- || Propellant : Propane, Butane, Dimethyl ether
- Colour : coloured
- Odour : solvent-like
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : -44 °C
- || Flash point : Not applicable
- Evaporation rate : Not applicable
- Flammability (solid, gas) : Extremely flammable aerosol.
- Upper explosion limit / Upper flammability limit : 18.6 %(V)
- Lower explosion limit / Lower flammability limit : 1.5 %(V)
- Vapour pressure : 3,600 hPa (20 °C)
- Relative vapour density : Not applicable
- Relative density : No data available
- || Density : No data available

LSPR-R9005-JETBLACK-MATT-400ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2019
11.0	22.05.2019	665410-00003	Date of first issue: 30.11.2012

Solubility(ies)
Water solubility : immiscible, partly miscible

Partition coefficient: n-octanol/water : Not applicable

Auto-ignition temperature : 235 °C

Decomposition temperature : No data available

Viscosity
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Extremely flammable aerosol.
Vapours may form explosive mixture with air.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
Can react with strong oxidizing agents.
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products

Thermal decomposition : Formaldehyde
Methanol

SECTION 11. TOXICOLOGICAL INFORMATION

Exposure routes : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

|| Not classified based on available information.

Product:

LSPR-R9005-JETBLACK-MATT-400ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2019
11.0	22.05.2019	665410-00003	Date of first issue: 30.11.2012

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:**Acetone:**

Acute oral toxicity : LD50 (Rat): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 7,426 mg/kg

Butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Dimethyl ether:

Acute inhalation toxicity : LC50 (Rat): 164000 ppm
Exposure time: 4 h
Test atmosphere: gas

Propane:

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm
Exposure time: 15 min
Test atmosphere: gas

Reaction mass of ethylbenzene and xylene:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: Directive 67/548/EEC, Annex V, B.1.
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Remarks: Based on data from similar materials

n-Butyl acetate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21.1 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

LSPR-R9005-JETBLACK-MATT-400ML

Version 11.0 Revision Date: 22.05.2019 SDS Number: 665410-00003 Date of last issue: 01.03.2019
Date of first issue: 30.11.2012

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

2-Methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC0 (Rat): 9.48 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

Isobutyl methyl ketone:

Acute oral toxicity : LD50 (Rat): 2,080 mg/kg

Acute inhalation toxicity : LC50 (Rat): 11.6 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Ethanol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 124.7 mg/l
Exposure time: 4 h
Test atmosphere: vapour

butyl glycollate:

Acute oral toxicity : LD50 (Rat): 4,595 mg/kg

Acute inhalation toxicity : LC0 (Rat): \geq 6.2 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Components:**Acetone:**

Assessment : Repeated exposure may cause skin dryness or cracking.

Reaction mass of ethylbenzene and xylene:

Species : Rabbit
Result : Skin irritation
Remarks : Based on data from similar materials

LSPR-R9005-JETBLACK-MATT-400ML

Version 11.0 Revision Date: 22.05.2019 SDS Number: 665410-00003 Date of last issue: 01.03.2019
Date of first issue: 30.11.2012

n-Butyl acetate:

Species : Rabbit
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

2-Methoxy-1-methylethyl acetate:

Species : Rabbit
Result : No skin irritation

Isobutyl methyl ketone:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.
Remarks : Based on harmonised classification in EU regulation
1272/2008, Annex VI

Ethanol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

butyl glycollate:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:**Acetone:**

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Method : OECD Test Guideline 405

Reaction mass of ethylbenzene and xylene:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Remarks : Based on data from similar materials

n-Butyl acetate:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

LSPR-R9005-JETBLACK-MATT-400ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2019
11.0	22.05.2019	665410-00003	Date of first issue: 30.11.2012

2-Methoxy-1-methylethyl acetate:

Species	:	Rabbit
Result	:	No eye irritation

Isobutyl methyl ketone:

Result	:	Irritation to eyes, reversing within 21 days
--------	---	--

Ethanol:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days
Method	:	OECD Test Guideline 405

butyl glycollate:

Species	:	Rabbit
Result	:	Irreversible effects on the eye

Respiratory or skin sensitisation
Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:
Acetone:

Test Type	:	Maximisation Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Result	:	negative

Reaction mass of ethylbenzene and xylene:

Test Type	:	Local lymph node assay (LLNA)
Exposure routes	:	Skin contact
Species	:	Mouse
Result	:	negative
Remarks	:	Based on data from similar materials

n-Butyl acetate:

Test Type	:	Maximisation Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Result	:	negative

2-Methoxy-1-methylethyl acetate:

Test Type	:	Maximisation Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406

LSPR-R9005-JETBLACK-MATT-400ML

Version 11.0 Revision Date: 22.05.2019 SDS Number: 665410-00003 Date of last issue: 01.03.2019
Date of first issue: 30.11.2012

Result : negative

Isobutyl methyl ketone:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Ethanol:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Result : negative

butyl glycollate:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Chronic toxicity**Germ cell mutagenicity**

|| Not classified based on available information.

Components:**Acetone:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

Butane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat

LSPR-R9005-JETBLACK-MATT-400ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2019
11.0	22.05.2019	665410-00003	Date of first issue: 30.11.2012

Application Route: inhalation (gas)
 Method: OECD Test Guideline 474
 Result: negative
 Remarks: Based on data from similar materials

Dimethyl ether:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative

Test Type: Chromosome aberration test in vitro
 Method: OECD Test Guideline 473
 Result: negative

Test Type: In vitro mammalian cell gene mutation test
 Method: OECD Test Guideline 476
 Result: negative

Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in *Drosophila melanogaster* (in vivo)
 Application Route: inhalation (gas)
 Result: negative

Propane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cyto-genetic assay)
 Species: Rat
 Application Route: inhalation (gas)
 Method: OECD Test Guideline 474
 Result: negative

Reaction mass of ethylbenzene and xylene:

Genotoxicity in vitro : Test Type: In vitro sister chromatid exchange assay in mam-malian cells
 Result: negative
 Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
 Result: negative
 Remarks: Based on data from similar materials

Test Type: Bacterial reverse mutation assay (AMES)
 Result: negative
 Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
 Species: Rat
 Application Route: Intraperitoneal injection
 Result: negative
 Remarks: Based on data from similar materials

LSPR-R9005-JETBLACK-MATT-400ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2019
11.0	22.05.2019	665410-00003	Date of first issue: 30.11.2012

II
n-Butyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

2-Methoxy-1-methylethyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Isobutyl methyl ketone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: equivocal

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative

Test Type: Saccharomyces cerevisiae, gene mutation assay (in vitro)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Ethanol:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Ingestion
Result: equivocal

LSPR-R9005-JETBLACK-MATT-400ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2019
11.0	22.05.2019	665410-00003	Date of first issue: 30.11.2012

||

butyl glycollate:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Mouse Lymphoma
Method: OECD Test Guideline 476
Result: negative

Carcinogenicity

|| Not classified based on available information.

Components:**Acetone:**

Species : Mouse
Application Route : Skin contact
Exposure time : 424 days
Result : negative

Dimethyl ether:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 2 Years
Result : negative

|| **Reaction mass of ethylbenzene and xylene:**

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative
Remarks : Based on data from similar materials

2-Methoxy-1-methylethyl acetate:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 2 Years
Result : negative
Remarks : Based on data from similar materials

|| **Isobutyl methyl ketone:**

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 2 Years
Method : OECD Test Guideline 451
Result : positive

LSPR-R9005-JETBLACK-MATT-400ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2019
11.0	22.05.2019	665410-00003	Date of first issue: 30.11.2012

Remarks	:	The mechanism or mode of action may not be relevant in humans.
Species	:	Mouse
Application Route	:	inhalation (vapour)
Exposure time	:	2 Years
Method	:	OECD Test Guideline 451
Result	:	positive
Remarks	:	The mechanism or mode of action may not be relevant in humans.

Reproductive toxicity

|| Not classified based on available information.

Components:
Acetone:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Butane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Dimethyl ether:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

LSPR-R9005-JETBLACK-MATT-400ML

Version 11.0 Revision Date: 22.05.2019 SDS Number: 665410-00003 Date of last issue: 01.03.2019
Date of first issue: 30.11.2012

Propane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Reaction mass of ethylbenzene and xylene:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: Based on data from similar materials

n-Butyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 416
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

2-Methoxy-1-methylethyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 416
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

LSPR-R9005-JETBLACK-MATT-400ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2019
11.0	22.05.2019	665410-00003	Date of first issue: 30.11.2012

Isobutyl methyl ketone:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Ethanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Mouse
Application Route: Ingestion
Result: negative

butyl glycollate:

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: positive

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

STOT - single exposure

|| May cause drowsiness or dizziness.

Components:
Acetone:

Assessment : May cause drowsiness or dizziness.

Butane:

Assessment : May cause drowsiness or dizziness.

Dimethyl ether:

Assessment : May cause drowsiness or dizziness.

Propane:

Assessment : May cause drowsiness or dizziness.

Reaction mass of ethylbenzene and xylene:

|| Assessment : May cause respiratory irritation.

n-Butyl acetate:

Assessment : May cause drowsiness or dizziness.

LSPR-R9005-JETBLACK-MATT-400ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2019
11.0	22.05.2019	665410-00003	Date of first issue: 30.11.2012

2-Methoxy-1-methylethyl acetate:

Assessment : May cause drowsiness or dizziness.

Isobutyl methyl ketone:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:
Reaction mass of ethylbenzene and xylene:

Exposure routes : inhalation (vapour)
 Target Organs : Auditory system
 Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Repeated dose toxicity
Components:
Acetone:

Species : Rat
 NOAEL : 900 mg/kg
 LOAEL : 1,700 mg/kg
 Application Route : Ingestion
 Exposure time : 90 Days

Species : Rat
 NOAEL : 45 mg/l
 Application Route : inhalation (vapour)
 Exposure time : 8 Weeks

Butane:

Species : Rat
 NOAEL : 9000 ppm
 Application Route : inhalation (gas)
 Exposure time : 6 Weeks
 Method : OECD Test Guideline 422

Dimethyl ether:

Species : Rat
 NOAEL : 47.11 mg/l
 Application Route : inhalation (vapour)
 Exposure time : 2 yr

Propane:

Species : Rat
 NOAEL : 7.214 mg/l
 Application Route : inhalation (gas)

LSPR-R9005-JETBLACK-MATT-400ML

Version 11.0 Revision Date: 22.05.2019 SDS Number: 665410-00003 Date of last issue: 01.03.2019
Date of first issue: 30.11.2012

Exposure time : 6 Weeks
Method : OECD Test Guideline 422

Reaction mass of ethylbenzene and xylene:

Species : Rat
LOAEL : > 0.2 - 1 mg/l
Application Route : inhalation (vapour)
Exposure time : 13 Weeks
Remarks : Based on data from similar materials

Species : Rat
LOAEL : > 100 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Remarks : Based on data from similar materials

n-Butyl acetate:

Species : Rat
NOAEL : 2.4 mg/l
Application Route : inhalation (vapour)
Exposure time : 90 Days

2-Methoxy-1-methylethyl acetate:

Species : Rat
NOAEL : > 1,000 mg/kg
Application Route : Ingestion
Exposure time : 41 - 45 Days
Method : OECD Test Guideline 422

Species : Mouse
NOAEL : 1.62 mg/l
Application Route : inhalation (vapour)
Exposure time : 2 yr
Remarks : Based on data from similar materials

Species : Rabbit
NOAEL : > 1,838 mg/kg
Application Route : Skin contact
Exposure time : 90 Days
Remarks : Based on data from similar materials

Isobutyl methyl ketone:

Species : Rat
NOAEL : 4.106 mg/l
Application Route : inhalation (vapour)
Exposure time : 14 Weeks

Species : Rat
NOAEL : 250 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

LSPR-R9005-JETBLACK-MATT-400ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2019
11.0	22.05.2019	665410-00003	Date of first issue: 30.11.2012

Ethanol:

Species	: Rat
NOAEL	: 1,280 mg/kg
LOAEL	: 3,156 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days

butyl glycollate:

Species	: Rat
NOAEL	: 1,000 mg/kg
Application Route	: Ingestion
Exposure time	: 29 Days
Method	: OECD Test Guideline 407

Aspiration toxicity

Not classified based on available information.

Components:
Acetone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

Reaction mass of ethylbenzene and xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Isobutyl methyl ketone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity
Components:
Acetone:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia pulex (Water flea)): 8,800 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	: NOEC (Pseudokirchneriella subcapitata (green algae)): 7,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): >= 79 mg/l Exposure time: 21 d Method: OECD Test Guideline 211

LSPR-R9005-JETBLACK-MATT-400ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2019
11.0	22.05.2019	665410-00003	Date of first issue: 30.11.2012

Toxicity to microorganisms : EC50: 61,150 mg/l
 Exposure time: 30 min
 Method: ISO 8192

Dimethyl ether:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 4,100 mg/l
 Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 4,400 mg/l
 Exposure time: 48 h

Toxicity to microorganisms : EC10 (Pseudomonas putida): > 1,600 mg/l

Reaction mass of ethylbenzene and xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 1 - 10 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1 - 10 mg/l
 Exposure time: 24 h
 Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 1 - 10 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201
 Remarks: Based on data from similar materials

EC10 (Pseudokirchneriella subcapitata (green algae)): > 1 - 10 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201
 Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): > 0.1 - 1 mg/l
 Exposure time: 35 d
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EL10 (Daphnia magna (Water flea)): > 1 - 10 mg/l
 Exposure time: 21 d
 Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 10 - 100 mg/l
 Exposure time: 28 d
 Remarks: Based on data from similar materials

n-Butyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l
 Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia sp. (water flea)): 44 mg/l

LSPR-R9005-JETBLACK-MATT-400ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2019
11.0	22.05.2019	665410-00003	Date of first issue: 30.11.2012

aquatic invertebrates	Exposure time: 48 h
Toxicity to algae/aquatic plants	: ErC50 (Pseudokirchneriella subcapitata (green algae)): 397 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
	NOEC (Pseudokirchneriella subcapitata (green algae)): 196 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 23.2 mg/l Exposure time: 21 d Method: OECD Test Guideline 211 Remarks: Based on data from similar materials
Toxicity to microorganisms	: IC50 (Tetrahymena pyriformis): 356 mg/l Exposure time: 40 h

2-Methoxy-1-methylethyl acetate:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 - 180 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 500 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	: ErC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l Exposure time: 96 h Method: OECD Test Guideline 201
	NOEC (Pseudokirchneriella subcapitata (algae)): > 1,000 mg/l Exposure time: 96 h Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): \geq 100 mg/l Exposure time: 21 d Method: OECD Test Guideline 211
Toxicity to microorganisms	: EC10: > 1,000 mg/l Exposure time: 0.5 h

Isobutyl methyl ketone:

Toxicity to fish	: LC50 (Danio rerio (zebra fish)): > 179 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 200 mg/l Exposure time: 48 h

LSPR-R9005-JETBLACK-MATT-400ML

Version 11.0 Revision Date: 22.05.2019 SDS Number: 665410-00003 Date of last issue: 01.03.2019
 Date of first issue: 30.11.2012

Method: OECD Test Guideline 202

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 30 mg/l
 Exposure time: 21 d

Ethanol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l
 Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia (water flea)): > 1,000 mg/l
 Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l
 Exposure time: 72 h

EC10 (Chlorella vulgaris (Fresh water algae)): 11.5 mg/l
 Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 9.6 mg/l
 Exposure time: 9 d

Toxicity to microorganisms : EC50 (Pseudomonas putida): 6,500 mg/l
 Exposure time: 16 h

butyl glycollate:

Toxicity to fish : LC0 (Leuciscus idus (Golden orfe)): >= 50 mg/l
 Exposure time: 48 h
 Method: DIN 38412

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 280 mg/l
 Exposure time: 24 h
 Method: DIN 38412

Toxicity to algae/aquatic plants : EC10 (Lemna gibba (gibbous duckweed)): > 87.4 mg/l
 Exposure time: 7 d

Toxicity to microorganisms : EC50 (Pseudomonas putida): 2,320 mg/l
 Exposure time: 18 h

Persistence and degradability
Components:
Acetone:

Biodegradability : Result: Readily biodegradable.
 Biodegradation: 91 %
 Exposure time: 28 d

Butane:

Biodegradability : Result: Readily biodegradable.

LSPR-R9005-JETBLACK-MATT-400ML

Version 11.0 Revision Date: 22.05.2019 SDS Number: 665410-00003 Date of last issue: 01.03.2019
Date of first issue: 30.11.2012

Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Dimethyl ether:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Propane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Reaction mass of ethylbenzene and xylene:

Biodegradability : Result: Readily biodegradable.
Remarks: Based on data from similar materials

n-Butyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

2-Methoxy-1-methylethyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Isobutyl methyl ketone:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Ethanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 84 %
Exposure time: 20 d

butyl glycollate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 81 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

LSPR-R9005-JETBLACK-MATT-400ML

Version 11.0 Revision Date: 22.05.2019 SDS Number: 665410-00003 Date of last issue: 01.03.2019
Date of first issue: 30.11.2012

Bioaccumulative potential**Components:****Acetone:**

Partition coefficient: n-octanol/water : log Pow: -0.27 - -0.23

Butane:

Partition coefficient: n-octanol/water : log Pow: 2.31

Dimethyl ether:

Partition coefficient: n-octanol/water : log Pow: 0.2

Reaction mass of ethylbenzene and xylene:

Partition coefficient: n-octanol/water : log Pow: 3.49

n-Butyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2.3

2-Methoxy-1-methylethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 1.2

Isobutyl methyl ketone:

Partition coefficient: n-octanol/water : log Pow: 1.9

Ethanol:

Partition coefficient: n-octanol/water : log Pow: -0.35

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

LSPR-R9005-JETBLACK-MATT-400ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2019
11.0	22.05.2019	665410-00003	Date of first issue: 30.11.2012

Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1

IATA-DGR

UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**ADG**

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
Hazchem Code : 2YE

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

LSPR-R9005-JETBLACK-MATT-400ML

Version 11.0 Revision Date: 22.05.2019 SDS Number: 665410-00003 Date of last issue: 01.03.2019
Date of first issue: 30.11.2012

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture**

Standard for the Uniform Scheduling of Medicines and Poisons : Schedule 5

Prohibition/Licensing Requirements : There is no applicable prohibition or notification/licensing requirements, including for carcinogens under Commonwealth, State or Territory legislation.

The components of this product are reported in the following inventories:

AICS : All ingredients listed or exempt.

SECTION 16. OTHER INFORMATION**Further information**

Revision Date : 22.05.2019

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.

ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
AU OEL / TWA : Exposure standard - time weighted average
AU OEL / STEL : Exposure standard - short term exposure limit

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada);

LSPR-R9005-JETBLACK-MATT-400ML

Version	Revision Date:	SDS Number:	Date of last issue: 01.03.2019
11.0	22.05.2019	665410-00003	Date of first issue: 30.11.2012

ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

AU / EN