

Pipe Sealant

Version 4.5 Revision Date: 16.05.2019 SDS Number: 855693-00003 Date of last issue: 18.03.2019
Date of first issue: 06.10.2010

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Pipe Sealant

Product code : 0893 577 050

Manufacturer or supplier's details

Company : Wurth Australia Pty Ltd

Address : 2/1 Healey Road
Dandenong South, Victoria, 3175

Telephone : +61 3 8788 1111

Emergency telephone number : 1300 657 765. Advisory office in case of poisoning - National Poisons Centre: 131 126

E-mail address : prodsafe@wuerth.com

Recommended use of the chemical and restrictions on use

Recommended use : Adhesives

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
2'-Phenylacetohydrazide	114-83-0	< 1
Cumene hydroperoxide	80-15-9	< 1

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical

Pipe Sealant

Version	Revision Date:	SDS Number:	Date of last issue: 18.03.2019
4.5	16.05.2019	855693-00003	Date of first issue: 06.10.2010

- advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : None known.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Silicon oxides
Carbon oxides
Nitrogen oxides (NO_x)
Sulphur oxides
Fluorine compounds
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Pipe Sealant

Version	Revision Date:	SDS Number:	Date of last issue: 18.03.2019
4.5	16.05.2019	855693-00003	Date of first issue: 06.10.2010

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Avoid inhalation of vapour or mist.
Do not swallow.
Avoid contact with eyes.
Avoid prolonged or repeated contact with skin.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

Pipe Sealant

Version	Revision Date:	SDS Number:	Date of last issue: 18.03.2019
4.5	16.05.2019	855693-00003	Date of first issue: 06.10.2010

- Conditions for safe storage : Keep in properly labelled containers.
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
- Recommended storage temperature : 20 °C
- Storage period : 12 Months
-

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Contains no substances with occupational exposure limit values.

- Engineering measures** : Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

- Filter type : Particulates type

Hand protection

- Material : Nitrile rubber
Break through time : 480 min
Glove thickness : > 0.4 mm
Directive : DIN EN 374

- Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

- Eye protection : Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.
Wear the following personal protective equipment:
Safety glasses
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.

- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective

Pipe Sealant

Version 4.5 Revision Date: 16.05.2019 SDS Number: 855693-00003 Date of last issue: 18.03.2019
Date of first issue: 06.10.2010

Method: Brookfield

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Can react with strong oxidizing agents.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Exposure routes : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:**2'-Phenylacetohydrazide:**

Acute oral toxicity : LD50 (Mouse): 270 mg/kg

Pipe Sealant

Version	Revision Date:	SDS Number:	Date of last issue: 18.03.2019
4.5	16.05.2019	855693-00003	Date of first issue: 06.10.2010

Acute dermal toxicity : LD50 (Rabbit): > 300 - 2,000 mg/kg
Remarks: Based on data from similar materials

Cumene hydroperoxide:

Acute oral toxicity : LD50 (Rat): 1,470 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 0.51 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgement
Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

Acute dermal toxicity : LD50 (Rabbit): 133.6 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:**2'-Phenylacetohydrazide:**

Species : Rabbit
Result : Skin irritation
Remarks : Based on data from similar materials

Cumene hydroperoxide:

Species : Rabbit
Result : Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Not classified based on available information.

Components:**2'-Phenylacetohydrazide:**

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Remarks : Based on data from similar materials

Cumene hydroperoxide:

Species : Rabbit
Result : Irreversible effects on the eye

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Pipe Sealant

Version 4.5 Revision Date: 16.05.2019 SDS Number: 855693-00003 Date of last issue: 18.03.2019
Date of first issue: 06.10.2010

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Components:

2'-Phenylacetohydrazide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: positive

Cumene hydroperoxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Skin contact
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

2'-Phenylacetohydrazide:

Species : Mouse
Application Route : Ingestion
Exposure time : 2 years
Result : positive

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies (oral)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

Components:

Cumene hydroperoxide:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:

Cumene hydroperoxide:

Exposure routes : inhalation (vapour)
Target Organs : Lungs

Pipe Sealant

Version	Revision Date:	SDS Number:	Date of last issue: 18.03.2019
4.5	16.05.2019	855693-00003	Date of first issue: 06.10.2010

Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Repeated dose toxicity**Components:****Cumene hydroperoxide:**

Species : Rat
NOAEL : 0.031 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 90 Days

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****2'-Phenylacetohydrazide:**

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 0.1 - 1 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Cumene hydroperoxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 3.9 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 18.84 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 3.1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): 1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Persistence and degradability**Components:****2'-Phenylacetohydrazide:**

Biodegradability : Result: Readily biodegradable.
Remarks: Based on data from similar materials

Pipe Sealant

Version 4.5 Revision Date: 16.05.2019 SDS Number: 855693-00003 Date of last issue: 18.03.2019
Date of first issue: 06.10.2010

Cumene hydroperoxide:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 3 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Bioaccumulative potential**Components:****Cumene hydroperoxide:**

Partition coefficient: n- : log Pow: 1.6
octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.
Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**ADG**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Pipe Sealant

Version Revision Date: SDS Number: Date of last issue: 18.03.2019
4.5 16.05.2019 855693-00003 Date of first issue: 06.10.2010

Standard for the Uniform : No poison schedule number allocated
Scheduling of Medicines and
Poisons

Prohibition/Licensing Requirements : There is no applicable prohibition or
notification/licensing requirements,
including for carcinogens under
Commonwealth, State or Territory
legislation.

The components of this product are reported in the following inventories:

AICS : All ingredients listed or exempt.

SECTION 16. OTHER INFORMATION**Further information**

Revision Date : 16.05.2019

Sources of key data used to : Internal technical data, data from raw material SDSs, OECD
compile the Safety Data eChem Portal search results and European Chemicals Agen-
Sheet cy, <http://echa.europa.eu/>

Date format : dd.mm.yyyy

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship;

Pipe Sealant

Version	Revision Date:	SDS Number:	Date of last issue: 18.03.2019
4.5	16.05.2019	855693-00003	Date of first issue: 06.10.2010

REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

AU / EN