

Rost off PLUS 300ML

Version 7.1 Revision Date: 23.11.2022 SDS Number: 10657808-00010 Date of last issue: 08.04.2022
Date of first issue: 29.09.2010

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Rost off PLUS 300ML

Product code : 0890 200

Manufacturer or supplier's details

Company : Wurth Australia Pty. Ltd.

Address : Building 5, 43 - 63 Princes Highway
Dandenong South, VIC 3175

Telephone : +61 3 8788 1111

Emergency telephone number : 1300 657 765. Advisory office in case of poisoning - National
Poisons Centre: 131 126

E-mail address : prodsafe@wurth.com

Recommended use of the chemical and restrictions on use

Recommended use : Solvent
Detergent

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Aerosols : Category 1

Specific target organ toxicity - single exposure : Category 3

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H336 May cause drowsiness or dizziness.

Supplemental Hazard Statements : AUH066 Repeated exposure may cause skin dryness or crack-
ing.

Precautionary statements : **Prevention:**

Rost off PLUS 300ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.04.2022
7.1	23.11.2022	10657808-00010	Date of first issue: 29.09.2010

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing spray.
 P271 Use only outdoors or in a well-ventilated area.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

Storage:

P405 Store locked up.
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	>= 60 -<= 100
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	>= 10 -< 30
Isobutane	75-28-5	< 10
Propane	74-98-6	< 10
Carbon dioxide	124-38-9	< 10
Methyl salicylate	119-36-8	< 1

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
 When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
 Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.
 Remove contaminated clothing and shoes.
 Get medical attention.
 Wash clothing before reuse.

Rost off PLUS 300ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.04.2022
7.1	23.11.2022	10657808-00010	Date of first issue: 29.09.2010

- Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
-

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
- Hazchem Code : 2YE
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency measures : Remove all sources of ignition.
Use personal protective equipment.

Rost off PLUS 300ML

Version Revision Date: SDS Number: Date of last issue: 08.04.2022
7.1 23.11.2022 10657808-00010 Date of first issue: 29.09.2010

place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

Conditions for safe storage : Store locked up.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight.

Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable liquids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Explosives

Recommended storage temperature : 10 - 40 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	TWA	900 mg/m ³	AU OEL
		TWA (Mist)	5 mg/m ³	AU OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	TWA (Mist)	5 mg/m ³	AU OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
Isobutane	75-28-5	STEL	1,000 ppm	ACGIH
Carbon dioxide	124-38-9	TWA	5,000 ppm 9,000 mg/m ³	AU OEL
		STEL	30,000 ppm 54,000 mg/m ³	AU OEL
		TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH

Engineering measures : Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.

Rost off PLUS 300ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.04.2022
7.1	23.11.2022	10657808-00010	Date of first issue: 29.09.2010

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Material : Nitrile rubber
Break through time : < 480 min
Glove thickness : 0.45 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Propellant : Isobutane, Propane, Carbon dioxide, Butane

Colour : light yellow

Odour : mint-like

Odour Threshold : No data available

Rost off PLUS 300ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.04.2022
7.1	23.11.2022	10657808-00010	Date of first issue: 29.09.2010

pH	:	substance/mixture is non-soluble (in water)
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	110 °C
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	11 %(V)
Lower explosion limit / Lower flammability limit	:	1 %(V)
Vapour pressure	:	Not applicable
Relative vapour density	:	Not applicable
Density	:	0.778 g/cm ³ (20 °C) Method: DIN 51757
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	< 7 mm ² /s
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reac-	:	Extremely flammable aerosol.

Rost off PLUS 300ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.04.2022
7.1	23.11.2022	10657808-00010	Date of first issue: 29.09.2010

tions	Vapours may form explosive mixture with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Exposure routes	: Inhalation Skin contact Ingestion Eye contact
-----------------	--

Acute toxicity

Not classified based on available information.

Components:**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Remarks: Based on data from similar materials
Acute inhalation toxicity	: LC50 (Rat): > 4,951 mg/m ³ Exposure time: 4 h Test atmosphere: vapour Assessment: The substance or mixture has no acute inhalation toxicity Remarks: Based on data from similar materials
Acute dermal toxicity	: LD50 (Rabbit): > 3,160 mg/kg Assessment: The substance or mixture has no acute dermal toxicity Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated light paraffinic:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Remarks: Based on data from similar materials
Acute inhalation toxicity	: LC50 (Rat): > 4 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg Remarks: Based on data from similar materials

Isobutane:

Rost off PLUS 300ML

Version 7.1 Revision Date: 23.11.2022 SDS Number: 10657808-00010 Date of last issue: 08.04.2022
Date of first issue: 29.09.2010

Acute inhalation toxicity : LC50 (Mouse): 260200 ppm
Exposure time: 4 h
Test atmosphere: gas

Propane:

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm
Exposure time: 15 min
Test atmosphere: gas

Carbon dioxide:

Acute inhalation toxicity : LC50 (Rat): 40000 - 50000 ppm
Exposure time: 30 min
Test atmosphere: vapour

Methyl salicylate:

Acute oral toxicity : LD50 (Rat): 890 mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Components:**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Species : Rabbit
Result : Mild skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Distillates (petroleum), hydrotreated light paraffinic:

Species : Rabbit
Result : No skin irritation

Methyl salicylate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated light paraffinic:

Species : Rabbit

Rost off PLUS 300ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.04.2022
7.1	23.11.2022	10657808-00010	Date of first issue: 29.09.2010

Result : No eye irritation

Methyl salicylate:

Species : Tissue Culture
Method : OECD Test Guideline 491

Result : Irreversible effects on the eye

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated light paraffinic:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : Based on data from similar materials

Methyl salicylate:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Result : positive

Assessment : Probability or evidence of low to moderate skin sensitisation rate in humans

Chronic toxicity**Germ cell mutagenicity**

Not classified based on available information.

Components:**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Rost off PLUS 300ML

Version 7.1 Revision Date: 23.11.2022 SDS Number: 10657808-00010 Date of last issue: 08.04.2022
Date of first issue: 29.09.2010

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

Distillates (petroleum), hydrotreated light paraffinic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Isobutane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Propane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative

Methyl salicylate:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Carcinogenicity

Not classified based on available information.

Components:**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Species : Rat
Application Route : inhalation (vapour)

Rost off PLUS 300ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.04.2022
7.1	23.11.2022	10657808-00010	Date of first issue: 29.09.2010

Exposure time : 105 weeks
Result : negative
Remarks : Based on data from similar materials

Methyl salicylate:

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

Reproductive toxicity

Not classified based on available information.

Components:**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: Based on data from similar materials

Isobutane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Propane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the

Rost off PLUS 300ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.04.2022
7.1	23.11.2022	10657808-00010	Date of first issue: 29.09.2010

ment reproduction/developmental toxicity screening test
 Species: Rat
 Application Route: inhalation (gas)
 Method: OECD Test Guideline 422
 Result: negative

Methyl salicylate:

Effects on fertility : Test Type: Three-generation reproduction toxicity study
 Species: Rat
 Application Route: Ingestion
 Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
 Species: Rat
 Application Route: Ingestion
 Result: positive
 Remarks: Based on data from similar materials

Test Type: Embryo-foetal development
 Species: Monkey
 Application Route: Ingestion
 Result: positive
 Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

STOT - single exposure

May cause drowsiness or dizziness.

Components:
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Assessment : May cause drowsiness or dizziness.

Isobutane:

Assessment : May cause drowsiness or dizziness.

Propane:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity
Components:
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species : Rat
 NOAEL : 10,186 mg/m³
 Application Route : inhalation (vapour)

Rost off PLUS 300ML

Version 7.1 Revision Date: 23.11.2022 SDS Number: 10657808-00010 Date of last issue: 08.04.2022
Date of first issue: 29.09.2010

Exposure time : 13 Weeks

Distillates (petroleum), hydrotreated light paraffinic:

Species : Rabbit
NOAEL : 1,000 mg/kg
Application Route : Skin contact
Exposure time : 4 Weeks
Method : OECD Test Guideline 410
Remarks : Based on data from similar materials

Species : Rat
NOAEL : > 980 mg/m³
Application Route : inhalation (dust/mist/fume)
Exposure time : 4 Weeks
Remarks : Based on data from similar materials

Isobutane:

Species : Rat
NOAEL : 9000 ppm
Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

Propane:

Species : Rat
NOAEL : 7.214 mg/l
Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

Methyl salicylate:

Species : Rat
NOAEL : 50 mg/kg
LOAEL : 250 mg/kg
Application Route : Ingestion
Exposure time : 2 yr

Aspiration toxicity

Not classified based on available information.

Components:**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Distillates (petroleum), hydrotreated light paraffinic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Rost off PLUS 300ML

Version 7.1 Revision Date: 23.11.2022 SDS Number: 10657808-00010 Date of last issue: 08.04.2022
Date of first issue: 29.09.2010

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 30 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 22 - 46 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- NOELR (Pseudokirchneriella subcapitata (green algae)): 1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated light paraffinic:

- Toxicity to daphnia and other aquatic invertebrates : LL50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Test substance: Water Accommodated Fraction

Carbon dioxide:

- Toxicity to fish : NOEC (Lepomis macrochirus (Bluegill sunfish)): > 100 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Rost off PLUS 300ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.04.2022
7.1	23.11.2022	10657808-00010	Date of first issue: 29.09.2010

Toxicity to daphnia and other aquatic invertebrates : NOEC (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Methyl salicylate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 10 - 100 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): 1.6 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): 0.79 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10 (Pseudomonas putida): 140 mg/l
Exposure time: 16 h

Persistence and degradability**Components:****Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Biodegradability : Result: Readily biodegradable.
Biodegradation: 89 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated light paraffinic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Isobutane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Propane:

Biodegradability : Result: Readily biodegradable.

Rost off PLUS 300ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.04.2022
7.1	23.11.2022	10657808-00010	Date of first issue: 29.09.2010

Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Methyl salicylate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 98.4 %
Exposure time: 28 d

Bioaccumulative potential**Components:****Isobutane:**

Partition coefficient: n-octanol/water : log Pow: 2.8

Carbon dioxide:

Partition coefficient: n-octanol/water : log Pow: 0.83

Methyl salicylate:

Partition coefficient: n-octanol/water : log Pow: 2.55

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)

SECTION 14. TRANSPORT INFORMATION**International Regulations**

Rost off PLUS 300ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.04.2022
7.1	23.11.2022	10657808-00010	Date of first issue: 29.09.2010

UNRTDG

UN number	: UN 1950
Proper shipping name	: AEROSOLS
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1

IATA-DGR

UN/ID No.	: UN 1950
Proper shipping name	: Aerosols, flammable
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: Flammable Gas
Packing instruction (cargo aircraft)	: 203
Packing instruction (passenger aircraft)	: 203

IMDG-Code

UN number	: UN 1950
Proper shipping name	: AEROSOLS
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1
EmS Code	: F-D, S-U
Marine pollutant	: no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**ADG**

UN number	: UN 1950
Proper shipping name	: AEROSOLS
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1
Hazchem Code	: 2YE

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture**

Standard for the Uniform Scheduling of Medicines and Poisons	: Schedule 5
--	--------------

Rost off PLUS 300ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.04.2022
7.1	23.11.2022	10657808-00010	Date of first issue: 29.09.2010

Prohibition/Licensing Requirements : There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 657.07 g/l

SECTION 16. OTHER INFORMATION
Further information

Revision Date : 23.11.2022

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
 AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.

ACGIH / TWA : 8-hour, time-weighted average
 ACGIH / STEL : Short-term exposure limit
 AU OEL / TWA : Exposure standard - time weighted average
 AU OEL / STEL : Exposure standard - short term exposure limit

AiIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Develop-

Rost off PLUS 300ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.04.2022
7.1	23.11.2022	10657808-00010	Date of first issue: 29.09.2010

ment; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

AU / EN